



NEVER BACKED DOWN

STOP & GO READY Red Palm, Green Back

BULLSEYE[™] Hand Protection Made for Demanding Environments SW[®] cut-resistant glove series with AxiFybr[®] engineered yarn technologies and protection features that enhance comfort and enable workers to perform at their best.

BULLSEYE









BULLSEYE^{**}

Cut-Resistant TPR Gloves

BULLSEYE				
C56231				
RATRICS	COATING Micro Porous Nitrile	_{GRIP} Sandy	FEATURES TPR AxiFybr® Extended Thumb Pad	COLOR RED HI-VIS YELLOW

Equipped with a Velcro[®] wrist closure, proprietary high flexibility TPR, padded palm, extended thumb crotch patch, and a distinct feature that allows for Stop & Go signaling at a distance ensures this tough glove holds up well against impacts in high-risk environments.

AxiFybr[®] engineered yarn technology provides greater comfort at ANSI A5 cut resistance while coating delivers ANSI 6 abrasion resistance for the maximum level of durability.

- 13-gauge AxiFybr[®] engineered yarn liner delivers comfort at high levels of cut resistance.
- Sandy microporous nitrile coating provides superior grip in oily and wet conditions.
- Advanced flexible TPR for ANSI level 2 impact
 resistance that does not sacrifice mobility or comfort.
- Palm padding to protect hands from repetitive impacts and vibrating tools.

APPLICATIONS:

- Demolition
- Drilling
- Heavy Construction
- Heavy Manufacturing
- Mining
- Oilfield
- Railroad
- Rigging

STOP & GO READY •

PALM PROTECTION .

impacts and vibrations

Padded palm to resist repetitive

THUMBS UP

Extended thumb

increased durability

crotch patch for

Red palm, green back for signaling at a distance

• ON GUARD

Advanced TPR provides back-of-hand protection and flexibility

PRODUCT ATTRIBUTES

SPECIFICATIONS	C56231	
PRODUCT TYPE:	Cut-Resistant	
CUT LEVEL:	ANSI A5 — EN388 E	
ABRASION LEVEL:	ANSI 6 — EN388 4	
LINER MATERIAL:	AxiFybr®	
COATING MATERIAL:	Micro Porous Nitrile	
LINER COLOR:	Yellow	
COATING COLOR:	Red	
GRIP FINISH:	Sandy	
CONSTRUCTION:	Knit	
FIT TYPE:	Hand Specific	
CUFF STYLE:	Velcro® Knit Wrist	
GAUGE:	13 Gauge	
LENGTH:	10.2"	

STANDARDS & CERTIFICATIONS

EN 420:2003+A1: 2009 EN 388:2016 21CFR 177.1520 Please visit swsafety.com/symbols for information on standards used in this document



C56221 ORDERING INFORMATION

C562313	M: 8	
C562314	L: 9	
C562315	XL: 10	
C562316	2XL: 11	
C562317	3XL: 12	

6 Pairs per Bag, 6 Bags per Case



LOCK IT IN -

for secure fit

Velcro[®] wrist closure