



NU15-RD-ECO-GR

ISO 374-1:2016/TYPE A



A J K L M N O P S T

EN388:2016



3101X

EN374-5:2016



ABRASION



PUNCTURE

# NEWTRILE®

## HANDLE THE HOSTILE

EcoTek®

Biodegradability Technology



### Protection for the Most Demanding Environments

The industry's first reusable chemical protection gloves with EcoTek® Biodegradability Technology. Advanced chemical protection now has a smaller carbon footprint.



# NEWTRILE

## Chemical-Resistant Gloves

featuring  
**EcoTek**

### NU15-RD-ECO-GR

15 MIL UNLINED NITRILE CHEMICAL RESISTANT GLOVES



**Unlined, hand specific, nitrile rubber chemical resistance gloves, case hardened for enhanced performance**

- 15 mil thick and 13 inch cuff length for added protection
- EcoTek® Biodegradability Technology accelerates landfill breakdown without any performance loss\*
- Embossed raised-diamond surface for wet/dry grip
- Case hardened for enhanced physical and chemical performance while providing easier and more comfortable donning and doffing

#### Ideal Applications:

- Boat Manufacturing
- Chemical
- Food
- Housekeeping
- Janitorial
- Machinery & Equipment
- Transportation

SW®  
33278 Central Avenue, Unit 102, Union City, CA 94587, USA  
Tel: +1.510.429.8692 | Fax: +1.510.487.5347

Trademarks and registered trademarks are the property of SW and its affiliates.  
©2022 SW. All rights reserved.



Raised diamond grip pattern

Smooth unlined inner surface for easy donning

13 inch cuff for added coverage and protection

#### PRODUCT ATTRIBUTES

SPECIFICATIONS	NU15-RD-ECO-GR
PRODUCT TYPE:	Chemical-Resistant
PUNCTURE LEVEL:	ANSI 2 — EN388 1
ABRASION LEVEL:	ANSI 6 — EN388 3
LINER MATERIAL:	Unlined
MATERIAL:	Nitrile with EcoTek®
COLOR:	Green
GRIP FINISH:	Raised Diamond
CONSTRUCTION:	Unsupported
FIT TYPE:	Hand Specific
CUFF STYLE:	Straight
THICKNESS:	15 mil
LENGTH:	13"
ORIGIN COUNTRY:	Sri Lanka

#### STANDARDS & CERTIFICATIONS

**FDA 21 CFR 177.2600**  
COMPONENT MATERIALS COMPLY WITH FDA REGULATIONS FOR FOOD CONTACT

Please visit [swsafety.com/symbols](http://swsafety.com/symbols) for information on standards used in this document.



#### NU15-RD-ECO-GR ORDERING INFORMATION

N505092	S: 7
N505093	M: 8
N505094	L: 9
N505095	XL: 10
N505096	2XL: 11

12 Pairs per Bag, 12 Bags per Case

\*ASTM D5526-12 is a standard test method for determining anaerobic biodegradation of plastics in accelerated landfill conditions. Current biodegradation results do not predict future results.

For samples visit  
[swsafety.com/newtrile](http://swsafety.com/newtrile)