

FEEL THE SW DIFFERENCE

DESIGNED TO ENHANCE WORKER PERFORMANCE.



PF-95OR

POWDER FREE ECOTEK BIODEGRADABLE NITRILE EXAM GLOVES WITH TRACTEK

ENGINEERED WITH HIGH DURABILITY, THESE BIODEGRADABLE GLOVES PROVIDE EXCEPTIONAL GRIP IN WET AND OILY CONDITIONS*

Hi-Vis orange color

TracTek technology for wet and dry grip

Beaded cuff allows easy

donning and doffing

- TracTek[®] high density pattern for grip in wet / oily conditions
- EcoTek[®] technology breaks down in landfills in less time
- Hi-Vis orange color
- Beaded cuff allows easy donning and doffing





Feel the

difference."





TECHNICAL DATA



PF-95OR

POWDER FREE ECOTEK BIODEGRADABLE NITRILE EXAM GLOVES WITH TRACTEK

PRODUCT DESCRIPTION

SPECIFICATIONS				
PRODUCT		PowerFor	m®	
GRADE		Powder-Free Exam		
MATERIAL		Nitrile		
THICKNESS	FINGER	5.9mil	0.15mm	
	PALM	5.1mil	0.13mm	
	CUFF	4.3mil	0.11mm	
COLOR		Orange		
SURFACE		Fully Textured		
LENGTH		9.5"	242mm	
WEIGHT		7.5g		
FIT TYPE		Ambidextrous		
CUFF TYPE		Beaded		
WATERTIGHT AQL		1.5		
ORIGIN COUNTRY		Thailand		

PHYSICAL PROPERTIES PRE-AGING PRE-AGING POST-AGING TENSILE 14 MPa STRENGTH: 14 MPa ELONGATION: 500%

INTEGRATED TECHNOLOGIES

ECOTEK Biodegradability Technology: 92.6% biodegradable in 2.5 years. ASTM D5526-12 test results do not predict future biodegradation.*

TRACTEK Grip Technology: Provides a highdensity pattern maximizes grip in wet or oily conditions.





* Specifications based on size Large glove

STANDARDS & CERTIFICATIONS

EN 420:2003 EN 455:2000-2015 EU 2016/425 Reach EU 1907/2006 ANSI/ISEA 105-2016 US/EU Food Contact EN ISO 374-52016 EN ISO 374-52016 UNIS C € 0493 C €

Please visit swsafety.com/symbols for information on standards used on this document.

ORDERING

ITEM NO.	SIZE	PALM WIDTH	PACKAGING
N991752	S 6½ – 7	3.3" 85mm	100 gloves per box 10 boxes per case
N991753	M 7½ – 8	3.7" 95mm	100 gloves per box 10 boxes per case
N991754	L 8½ – 9	4.3" 108mm	100 gloves per box 10 boxes per case
N991755	XL 9½ – 10	4.5" 114mm	100 gloves per box 10 boxes per case
N991756	2XL 10½ – 11	5.0" 127mm	100 gloves per box 10 boxes per case

APPLICATIONS

INDUSTRIAL Assembly	
Fabrication	
Food handling and packaging	
Janitorial maintenance	
Light machining operations	
Liquid handling	
Maintenance	
Oily or wet surfaces	
Painting	
Waste management	
EXAM Chemical handling	
Liquid Handling	

Keep out of sunlight. Store in a cool, dry place. Keep away from sources of ozone or ignition.

GREEN



R_N90175X0122



33278 Central Avenue, Unit 102, Union City, CA 94587, USA Tel: +1.510.429.8692 | Fax: +1.510.487.5347 Trademarks and registered trademarks are the property of SW and its affiliates ©2022 SW. All rights reserved.

*Under test method ASTM D5526-12, a standard test method for determining anaerobic biodegradation of plastics in accelerated landfill conditions. Current biodegredation results do not predict future results.